





说明:


1. 10个边孔的累计公差不能超过 $\pm 0.2\text{mm}$.
2. 材料规格: PS 黑色防静电, 厚度 0.35mm.
3. 13英寸卷轮卷装长度18.528米。(前段空包长度:0.264米, 零件包装长度:18.0米, 后段空包长度:0.265米)。
4. 纸箱装箱以不超过装箱线为准, 空余位置用塑料泡沫填充。
5. 包装数量: 900PCS/盘



卷装示意图仅供参考



载带在250mm长度以内最大弯曲度不超过1mm(见下图)。



PIN位	A	F	W
4	11.4	11.5	24
5	12.4		
6	13.4		
7	14.4		
8	15.4		
9	16.4	14.2	32
10	17.4		
11	18.4		
12	19.4		
13	20.4		
14	21.4	20.2	44
15	22.4		
16	23.4		
17	24.4		
18	25.4		
19	26.4		
20	27.4		
21	28.4		
22	29.4		
23	30.4		
24	31.4	26.2	56
25	32.4		
26	33.4		
27	34.4		
28	35.4		
29	36.4		
30	37.4		
31	38.4		
32	39.4		
33	40.4		

ALL LINK CONN. TECHNOLOGY CORP.

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: 包装图
X' ±2' X' X' ±0.5'	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO.
UNIT: mm [inch]	APPROVED BY: 邱国英	DATE : 2014-02-23	MOLD NO.
SCALE: 1:1	SIZE: A4		DRAW NO.
			SHEET NO. 1 OF 1