



REV.	ECN NO.	LOCATIONS	DESCRIPTION	DATE	CHANGER

特性: Specifications:
电器: Electrical:
接触阻抗: Contact Resistance
30 milliohms MAX
耐电压: Dielectric Withstanding Voltage:
500V AC AT Sea Level
绝缘阻抗: Insulation Resistance:
1000 MEGA ohms MIN
材料: Material:
塑胶: PBT
端子: Contact: Copper Alloy C2680H
铜壳/铁壳: Shell: Copper Alloy C2680H/SPCC
电镀: Finish:
端子: Contact: Plated Gold in Mating Area;
Tin/ Sn Solder Tails
接触点镀金. 脚镀锡
铜壳/铁壳: Shell:
Nickel Plating 镀镍
TUB481 -X - 08 X 0
① ② ③ ④ ⑤
① Series No.
② Plating code:
G= Gold flash
1= Selective 3u" Gold plated
2= Selective 30" Gold plated
③ No. of Contact:
④ OTHER OPTIONS:
0=White 1=black
⑤ **PACKING**
0= TRY

PCB.LAYOUT

GENERAL TOLERANCE		ALL LINK CONN. TECHNOLOGY CORP.					
X±	X°± 1°					TITLE: USB AF 8PIN DIP A TYPE RA	
X± 0.30	.X°±						
.XX± 0.20	.XX°±						
XXX± 0.10	.XXX°±						
CUSTOMER DRAWING		PART NO. TUB481-G-08XX	DWG. NO. 20121209				
APPROVED Kevin	CHECKED: Paul	DRAWN: frank	UNIT mm	SCALE: 1:1	SHEET: 1/1		
			PROJ. 	REV. B			